

## Product Datasheet

# 26-port Full Gigabit PoE Fiber Switch (ONV-H3024PF)



## OVERVIEW

The ONV-H3024PF is an unmanaged PoE fiber switch independently developed by ONV. It has 24\*10/100/1000M adaptive RJ45 ports and 2\*1000M uplink SFP ports. Port 1-24 can support IEEE 802.3 af/at PoE standard. Single port PoE power is up to 30W, and the max POE output power is 250W. As a PoE power supply device, it can automatically detect and recognize the power-receiving equipment that meets the standard and supply power through the network cable. It can supply power to POE terminal equipment such as wireless AP, IP camera, VoIP phone, video access control intercom, etc. through a network cable to meet the network environment that needs a high-density PoE power supply. It is suitable for hotels, campuses, factory quarters, and small and medium-sized enterprises to form an economy-efficient network. Unmanaged model, plug and play, no configuration, easy to use.

## FEATURE

### ■ Full Gigabit port

- ◇ Support IEEE 802.3x full-duplex flow control and Backpressure.
- ◇ Support non-blocking wire-speed forwarding for smoother transmission.
- ◇ Support the combination of RJ45 ports and Gigabit SFP ports to facilitate flexible networking and meet the networking requirements of various scenarios.

### ■ Intelligent PoE power supply

- ◇ Comply with IEEE 802.3 af/at PoE standard, automatically identify PoE devices for power supply, and not damage non-PoE devices.
- ◇ The PoE port supports the priority mechanism. When the remaining power is insufficient, the power of the high-priority port is given priority to avoid overloading of the device.
- ◇ 24\*10/100/1000Base-T RJ45 ports support PoE power, meeting the PoE power requirements of security monitoring, teleconferencing system, wireless coverage, and other scenarios.

### ■ Stable and reliable

- ◇ CCC, CE, FCC, RoHS.
- ◇ The user-friendly panel can show the device status through the LED indicator of PWR, Link, PoE.
- ◇ Self-developed power supply, high redundancy design, providing a long term and stable PoE power output.
- ◇ Low power consumption, with fan, galvanized steel casing, excellent heat dissipation to ensure the stable operation of the switch.

## TECHNICAL SPECIFICATION

Model	ONV-H3016PF	ONV-H3024PF
<b>Interface Characteristics</b>		
Fixed Port	16*10/100/1000Base-T PoE ports (Data/Power)	24*10/100/1000Base-T PoE ports (Data/Power)
	2*1000Base-X uplink SFP ports (Data)	2*1000Base-X uplink SFP ports (Data)
Ethernet Port	Port 1-16/ 1-24 support 10/100/1000Base-T auto-sensing, full/half duplex MDI/MDI-X self-adaption	
Twisted Pair Transmission	10BASE-T: Cat3, 4, 5 UTP(≤100 meters) 100BASE-TX: Cat5 or later UTP(≤100 meters) 1000BASE-T: Cat5e or later UTP(≤100 meters)	
SFP Slot Port	Gigabit SFP optical fiber interface, default not matching optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC)	
Optical Cable/ Distance	Multi-mode: 850nm / 0-550m, Single-mode: 1310nm / 0-40km, 1550nm/ 0-120km.	
<b>Chip Parameter</b>		
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T, IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T, IEEE802.3z 1000Base-X, IEEE802.3x	
Forwarding Mode	Store and Forward(Full Wire Speed)	
Switching Capacity	52Gbps (Non-blocking)	
Forwarding Rate@64byte	26.78Mpps	38.69Mpps
MAC	8K	
Buffer Memory	4M	
Jumbo Frame	10K	

LED Indicator	Power: PWR (Green), Network: Link (Green) PoE: PoE (Green), Fiber: G1/G2(Green), POE: PoE(Green)	
<b>PoE &amp; Power Supply</b>		
PoE Port	Port 1 to 16 IEEE 802.3 af/at	Port 1 to 24 IEEE 802.3 af/at
Power Supply Pin	1/2 (+) 3/6 (-)	
Max Power Per Port	30W, IEEE 802.3 af/at	
Total PWR / Input Voltage	250W /(AC100-240V)	
Power Consumption	Standby<15W, Full Load<240W	Standby<20W, Full Load<250W
Power Supply	Built-in power supply, AC100~240V 50-60Hz 4.1A	
<b>Physical Parameter</b>		
Operation TEMP / Humidity	-20°C~+55°C, 5%~90% RH Non condensing	
Storage TEMP / Humidity	-40°C~+75°C, 5%~95% RH Non condensing	
Dimension (L*W*H)	270*181*44.5mm	330*204*44mm
Net /Gross Weight	<1.7kg / <2.2kg	<3.0kg / <3.5kg
Installation	Desktop, wall mount, 19 inch 1U cabinet	
<b>Certification &amp; Warranty</b>		
Lightning Protection	Lightning protection: 4KV 8/20us, Protection level: IP30	
Certification	CCC, CE mark, commercial, CE/LVD EN62368-1, FCC Part 15 Class B, RoHS	
Warranty	1 year, lifelong maintenance.	

## ORDERING INFORMATION

Model	Description
ONV-H3016PF	Unmanaged PoE switch with 16*10/100/1000M RJ45 ports and 2*1000M uplink SFP ports. Port 1-16 can support IEEE 802.3 af/at PoE Standard. Built-in 250W power supply. Support 19-inch cabinet installation.
ONV-H3024PF	Unmanaged PoE switch with 24*10/100/1000M RJ45 ports and 2*1000M uplink SFP ports. Port 1-24 can support IEEE 802.3 af/at PoE Standard. Built-in 250W power supply. Support 19-inch cabinet installation.

## PACKING LIST

	Content	Qty	Unit
Packing List	26-port full gigabit PoE switch	1	SET
	AC Power Cable	1	PC
	Mounting Kits	1	SET
	User Guide	1	PC
	Warranty Card	1	PC

## OPTICAL MODULE

Product	Model	Description	Unit
1.25G Optical Module	2630	SFP optical module, 1.25G, multi mode dual fiber 850nm, transmission distance: 550m, LC interface, support DDM function, support hot plug and pull.	PC
	2632	SFP optical module, 1.25G, single-mode dual fiber 1310nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull.	PC

	2612-T	SFP optical module, 1.25G, single-mode single fiber TX1310nm/RX1550nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull.	PC
	2613-R	SFP optical module, 1.25G, single-mode single fiber TX1550nm/RX1310nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull.	PC
	2612-T-SC	SFP optical module, 1.25G, single-mode single fiber TX1310nm/RX1550nm, transmission distance: 20km, SC interface, support DDM function, support hot plug and pull.	PC
	2613-R-SC	SFP optical module, 1.25G, single-mode single fiber TX1550nm/RX1310nm, transmission distance: 20km, SC interface, support DDM function, support hot plug and pull.	PC
Power Module	2633	1.25G SFP optical module transfers to 10/100/1000M RJ45 port.	PC

## CONTACT US

**ONV** Optical Network Video Technologies (Shenzhen) Co., Ltd.

Tel: 0086-755-33376606

Fax: 0086-755-33376608

WeChat: ONV-PoE-IoT

Email: onv@onv.com.cn

Skype: onv@onv.com.cn

Website: www.onvcom.com

Headquarter Address: Room 1003, Block D, Terra Building, Futian District, Shenzhen, China

Factory Address: Floor 4-6, Building A, Senyutai Industrial Park, No. 111, Huaning Road, Xinhai

Community, Dalang Street, Longhua District, Shenzhen, China

